

Cabinet Water Softener

SKU **090006** K268-762-1035-WCBP — Pentair Autotrol Performa 268-762 EASY-IQ Control Valve



Cabinet system



Manual bypass valve (included)



Autotrol Performa 268-762 EASY-IQ head

Performance

Peak Flow Rate	Up to 40 Lpm (25 L resin) or 48 Lpm (30 L resin) — peak service flow, sustained for under 10 minutes
Continuous Flow Rate	20 Lpm (25 L resin) or 27 Lpm (30 L resin)
Pressure Drop	0.5 bar (service mode)
Inlet Pressure	2 – 6 bar

Control Valve

Valve	Pentair Autotrol Performa 268-762 EASY-IQ microprocessor control
Valve Flow Capacity	95 Lpm (5.7 m ³ /h) rated
Power Supply	230 V, 50 Hz — 30 W consumption
Regeneration Duration	80 – 110 minutes
Salt per Regeneration	2.5 – 4.8 kg
Water per Regeneration	0.25 m ³

Optional outdoor cabinet cover available on request.

Tank, Media & Cabinet

Tank Size	10" x 35" — cabinet-mounted
Resin Options	25 L or 30 L — Standard (Purolite C100E) or Chlorine Resistant
Cabinet	Weather-protective enclosure with integrated brine well and aircheck tube
Bypass	Manual bypass valve maintains water supply during servicing
Connections	3/4" inlet/outlet (adaptor kits available in 3/4" or 1")